



HIGH TEMPERATURE SILICONE SEALANT



Directions:

- All surfaces must be clean, free of dirt, oil, old silicone and other debris that could deter adhesion.
- Cut nozzle to desired opening size and cut tip off of cartridge.
- Run a continuous bead along surface, keeping the silicone tube ahead of nozzle.
- Tool to a smooth finish. Excess, uncured sealant can be removed with solvent.
- Allow **MASTERS® HIGH TEMPERATURE SILICONE SEALANT** to cure fully before exposing to water, approximately 24 hours (dries to the touch in approximately 30 minutes).
- Store in a cool dry place between 40°F & 90°F (4°C & 32°C)

MASTERS® HIGH TEMPERATURE SILICONE SEALANT creates a water tight, mildew and crack resistant seal. The re-sealable, removable cap keeps product from drying out after opening. It is oxygen sensor safe and can be used to replace cork, felt rubber or asbestos gaskets.

MASTERS® HIGH TEMPERATURE SILICONE SEALANT is rated for interior/exterior use from -85°F to +500°F (-65°C to +260°C) consistent or 600°F (316°C) intermittent. It is ideal for sealing around:

- Ovens
- Flues on gas appliances
- Metal Stacks
- Ductwork
- Tub/Shower Surrounds
- Kitchen and Bathroom Sinks
- Siding
- Window Frames
- Tiling
- Countertops

RED302 is NSF-51 listed

Catalogue Number	Description	Quantity per Case	Approximate Case Shipping Weight
RED 302	300ml Cartridge - Red	12	10.2 Lbs 4.6 KG
BLACK 302	300ml Cartridge - Black	12	10.2 Lbs 4.6 KG



G. F. THOMPSON CO. LTD.

The professional choice since 1947

1-800-499-3673

www.gfthompson.com

Canada

