

# MASTERS®

## PRO-DOPE® PTFE Pipe Thread Sealant



**NOT FOR USE ON Oxygen or Glycol Systems.**  
We recommend **MASTERS® ORANGE T-TAPE**.

**Directions:**

- Stir Well.
- Do NOT Dilute.
- Threads must be clean.
- Apply to male threads beginning at 2nd thread.

**MASTERS® PRO-DOPE®** is a non-toxic, non-corrosive, non-hardening paste. It effectively seals both metal and plastic threaded connections. It will not dry out, stain, harden or separate. Lubricates during assembly and can easily be disassembled even after years of service.

**MASTERS® PRO-DOPE®** effectively seals most liquids and gases against leakage to 10,000 psi and from -200°F to +400°F (-129°C to +204°C).

**Recommended for:**

- Acids (dilute)
- Air (compressed, gaseous)
- Aliphatic Solvents
- Alkalis (dilute)
- Ammonia
- Brine
- Carbon Dioxide
- Castor Oils
- Caustic Alkali (dilute)
- Corrosives
- Diesel Fuel Oil
- Gasoline
- Heating oils
- Helium (gaseous)
- Hydraulic Oils
- Inert Gases (gaseous)
- Jet Fuel (JP4,5&6)
- Kerosene
- Liquefied Petroleum Gases
- Manufactured Gases
- Mineral Oils
- Natural Gas (gaseous)
- Nitrogen (gaseous)
- Oils
- Petroleum Solvents
- Potable Water
- Propane
- Refrigerants (most)
- Steam
- Sugar (liquid)

Catalogue Number	Description	Quantity per Case	Approximate Case Shipping Weight	
PD250BT	250 ml (1/2 pt) Brush-Top Can	25	26 lbs	11.8 kg
PD500BT	500 ml (1 pt) Brush-Top Can	12	23 lbs	10.5 kg
PD1L	1 L (1 qt) Can	4	13 lbs	5.9 kg
PD20L	20 L (5 gal) Pail	1	55 lbs	25 kg



Certified to NSF/ANSI 61 & 372



Listed by Underwriters' Laboratories of Canada and the U.S.



**G. F. THOMPSON CO. LTD.**

The professional choice since 1947

1-800-499-3673

www.gfthompson.com

Canada

