



SILICONE SEALANT



MASTERS® SILICONE SEALANT creates a water tight, mildew and crack resistant seal. The re-sealable, removable cap keeps product from drying out after opening.

MASTERS® SILICONE SEALANT is rated for interior and exterior use from -50°F to 450°F (-45°C to +232°C). It is ideal for:

- Tub/Shower Surrounds
- Kitchen and Bathroom Sinks
- Siding
- Window Frames
- Tiling
- Countertops



Certified to NSF 51

Directions:

- All surfaces must be clean, free of dirt, oil, old silicone and other debris that could deter adhesion.
- Cut nozzle to desired opening size and cut tip off of cartridge.
- Run a continuous bead along surface, keeping the silicone tube ahead of nozzle.
- Tool to a smooth finish. Excess, uncured sealant can be removed with solvent.
- Allow **MASTERS® SILICONE SEALANT** to cure fully before exposing to water, approximately 24 hours (dries to the touch in approximately 30 minutes).
- Store in a cool dry place between 40°F & 90°F (4°C & 32°C).



Catalogue Number	Description	Quantity per Case	Approximate Case Shipping Weight	
SS80-W	80 ml Squeeze Tube - White	12	2.9 lbs	1.3 kg
SS80-C	80 ml Squeeze Tube - Clear	12	2.9 lbs	1.3 kg
SS300-W	300 ml Cartridge - White	12	10.2 lbs	4.6 kg
SS300-C	300 ml Cartridge - Clear	12	10.2 lbs	4.6 kg
SS300-T	300 ml Cartridge - Translucent	12	10.2 lbs	4.6 kg
SS300-B	300 ml Cartridge - Bone	12	10.2 lbs	4.6 kg
SS300-G	300 ml Cartridge - Grey	12	10.2 lbs	4.6 kg
SS300-AL	300 ml Cartridge - Aluminum	12	10.2 lbs	4.6 kg

G. F. THOMPSON CO. LTD.

The professional choice since 1947

1-800-499-3673

www.gfthompson.com

Canada

