



WHITE TAPE

Thread Sealing Tape

MASTERS[®] WHITE TAPE seals all metal and plastic threaded connections against leakage at temperatures from -400°F to +600°F (-240°C to +316°C).

MASTERS[®] WHITE TAPE is non-corrosive, non-flammable, clean, easy to use and is available in a wide range of widths and lengths. Joints disassemble easily, even after years of service.

Because it is chemically inert, **MASTERS[®] WHITE TAPE** is impervious to virtually everything including:

- Acids & Alkalis
- Air
- Ammonia
- Chlorine
- CO₂
- Fuels
- Gasoline
- Hydrocarbons
- Kerosene
- Nitrogen
- Oxygen
- Refrigerants (most)
- Solvents
- Steam
- Water



Directions:

- Make sure threads are clean and remove any shreds of previously applied tape.
- Beginning with the first thread of the male end, wrap tape in the direction of the thread spiral. Use enough for a good seal.
- Tighten the joint using a wrench.

Catalogue Number	Description	Quantity per Case	Approximate Case Shipping Weight
TWA240G	1/4" x 240" (0.63 cm x 6.1 m) Roll	12	0.5 lbs 0.2 kg
TWB240G	1/2" x 240" (1.27 cm x 6.1 m) Roll	12	0.7 lbs 0.3 kg
TWB480G	1/2" x 480" (1.27 cm x 12.19 m) Roll	200	10 lbs 4.5 kg
TWC480G	3/4" x 480" (1.91 cm x 12.19 m) Roll	12	1 lb 0.5 kg
TWD480G	1" x 480" (2.54 cm x 12.19 m) Roll	12	2 lbs 0.9 kg
TWB480P	1/2" x 480" (1.27 cm x 12.19 m) Roll Economy/Low Density	200	6 lbs 2.7 kg

G. F. THOMPSON CO. LTD.

The professional choice since 1947

1-800-499-3673

www.gfthompson.com

Canada

